
# How to tile onto...

# Cement Screed or Concrete using Natural Stone



- 1. Ensure cement screed surface or concrete floor is fully cured, flat, clean and free of grease before commencing.
- 2. If the floor is porous, prime the surface with diluted Nicobond Primer (ratio 4 volumes of water to 1 volume of Nicobond Primer).
- 3. It is recommended to use a white cement based adhesive for bonding limestone and other light coloured or translucent natural stones. Apply a suitable layer of the recommended adhesive to the surface using a notched trowel. Lightly comb through onto the surface to be tiled. Solidly bed tiles into adhesive using slight sliding action. Every so often use a spirit level or straight edge to check that the tiles fixed are flat. Allow to dry to recommended time.
- 4. Do not use spot or blob fixing method for these tiles as unsightly water marks or "shadowing" may appear on the surface. Slate products are varied and can be supplied in cut or cleaved format. Slate may be impervious or relatively porous.
- 4. Natural Stones and Slate may require sealing prior to grouting, follow the manufacturer's instructions ensuring the adhesive has fully cured prior to sealing the stone surface. In the case of impervious natural stones this period can extend over several weeks.
- 5. Fill the joints between tiles with the recommended grout using a float grouter. Remove surplus grout from the surface with a sponge and smooth the joints with a rounded stick to achieve an even better finish.
- \* Allow at least 6 weeks for structural concrete floors to cure and further 3 weeks for subsequently applied screed. In the event that a rapid setting cement replacement is used the drying time of screed will be greatly reduced. Refer to the Technical Team for further information.

#### Recommended Tile Adhesives



Nicobond Natural Stone Speedflex



Nicobond Rapidflex

#### Recommended Tile Grout



Nicobond Flexible Grout Plus



Nicobond Tilers Grout

#### Featured Products



Nicobond Starlike Extreme Performance Grout





#### Manufacturing Tiling Solutions Since 1958

### N&C Tiles & Bathrooms Trade Counters & Showrooms

1A - 1B Alexander Place Lower Park Road, New Southgate **London** N11 1ST Tel: 020 8361 6050

Tel: 020 8361 6050 Fax: 020 8361 4757

8 Ascent Park, Edinburgh Way Harlow, Essex CM20 2HW Tel: 01279 621980 Fax: 01279 621981

14 Meridian Trading Estate Bugsby Way, Charlton **London** SE7 7SJ Tel: 020 8269 5960 Fax: 020 8269 5961

1 Cliffside Trade Park, Motherwell Way **Lakeside**, West Thurrock Essex RM20 3XD

Essex RM20 3XD Tel: 01708 680180 Fax: 01708 680181 16 Arlington Business Park Whittle Way, **Stevenage** Hertfordshire SG1 2BD Tel: 01438 315400 Fax: 01438 740338

9 - 11 McDonalds Business Park Maylands, **Hemel Hempstead** Hertfordshire HP2 7EB Tel: 0845 2606 025 Fax: 0845 2606 026

8D Pompey Centre, Fratton Way Southsea, **Portsmouth** PO4 8TA Tel: 02392 894599 Fax: 02392 894598

5 Tower Court, St David's Road Swansea Enterprise Park **Swansea** SA6 8QL

Tel: 01792 797337 Fax: 01792 774019

## N&C Tiles & Bathrooms Distribution Centres, Trade Counters & Showrooms

N&C Building Materials 41 - 51 Freshwater Road Chadwell Heath

Romford, Essex RM8 1SP Tel: 020 8586 4600 Fax: 020 8586 4646

C1 Cothill Trading Estate Plympton, **Plymouth** PL7 1SR Tel: 01752 339724 Fax: 01752 342746

B1 - B3 Sneyd Trading Estate Sneyd Hill, Burslem **Stoke on Trent** ST6 2PA Tel: 01782 575727

26 Colquhoun Avenue Hillington, **Glasgow** G52 4BN Tel: 0141 880 1200

Fax: 01782 575641

Fax: 0141 880 1212

4 Waterloo Industrial Estate Flanders Road, Hedge End **Southampton** SO30 2QT Tel: 01489 779700 Fax: 01489 779701

3 - 4 Cardiff Trade Park Hadfield Road, **Cardiff** CF11 8AQ Tel: 02920 390146 Fax: 02920 224356

2 City Park, Industrial Estate Gelderd Road, **Leeds** LS12 6DR Tel: 0113 224 4630 Fax: 0113 224 4631

2 - 5 Altbarn Close Wyncolls Road, Severalls Park **Colchester**, Essex CO4 9HY Tel: 01206 844 161 Fax: 01206 845 878





